

### **STANDARD SWINGING SPEED GATE**

### VX-SPEED-SW-SS-550-01

Standard swinging speed gate with brushless motor, dual leaf, single or dual sided, bi-directional, 304 stainless steel cover and body, with anti-tail gating, anti-reverse passing, anti-clamping, and illegal entry alarm.



# **Specifications**

#### **OPERATIONAL**

Passage width
Opening Speed
Fastest Opening Speed
Passing Capacity
Mean Cycles Between
Failure
Motor
Positioning

550mm ~ 900mm Adjustable 0.5 seconds 30 ~ 40 people / minute 3 million cycles

DC driven brushless motor Motor driven Unidirectional or bidirectional CE and FCC

### INTERFACE

Communication Input Reader RS485 Dry contact Built-in or Externa (Optional)

#### **SAFETY**

Sensors Anti-clamping

Anti-tailgating Anti-reverse passing Illegal entry alarm 6 Infrared sensors
Triple safety using
sensors, mechanical
and current detection
Yes
Yes
Audible and visual alarm

#### **STRUCTURE**

Material Body Thickness Cover Thickness Arm Material

**Amr Thickness** 

**Dimensions** 

IP Rating

Operating Temperature

304 brushed stainless steel

1.5mm 2.0mm

High impact polycarbonate, or Stainless steel (Optional) 12mm for HIP, 1.5mm for Stainless Steel

1600 x 210 x 1000 mm (L x W x H) for Machine of 2 x

Single Sided, Single Leaf Gates
IP55 suitable for indoor /
outdoor applications

-20 °C to +70 °C


#### **ELECTRICAL**


Operating voltage

Operating power

110VAC ~ 220VAC ±10% (50Hz ~ 60Hz) 30 Watt for single leaf, 60 Watt for dual leaf

## **Dimensions**





# Ordering Information

VX-SPEED-SW-SS-550-01 VX-SPEED-SW-SS-900-01 VX-SPEED-SW-SD-550-01 VX-SPEED-SW-SD-900-01 VX-SPEED-SSSW VX-SPEED-INRD-UPG VX-SPEED-EXRD-UPG Standard Dual x Single Sided Swing Speed Gate with 550mm Passage Width Standard Dual x Single Sided Swing Speed Gate with 900mm Passage Width Standard Single x Dual Sided Swing Speed Gate with 550mm Passage Width Standard Single x Dual Sided Swing Speed Gate with 900mm Passage Width Stainless Steel Swinging Arm \*

In-Built Reader Provision with Card Reader Upgrade for a Single Direction \*\*
External Reader Provision with Card Reader Upgrade for a Single Direction \*\*

- \* Stainless steel Arm marking to be confirmed with order, in case of dual leaf gates, 2 x SSSW items to be ordered with speed gate.
- \*\* Reader Type to be confirmed with order, in case of bi-directional readers, 2 x UPG items to be ordered with speed gate.