

STANDARD TRIPOD TURNSTILE

VX-TURN-SS-550-01

Compact Tripod Turnstile with Brush Motor, Single Sided, Bi-directional, 304 Stainless Steel Cover and Body, Dry contact for input signal, Outdoor Rated, with anti-tail gating, anti-reverse passing, anti-clamping, and illegal entry alarm



Specifications

OPERATIONAL

Passage width
Passing Capacity
Mean Cycles
Between Failure
Motor
Operation
Certification

STRUCTURE

Material Body Thickness Cover Thickness Arm Material Amr Thickness Dimensions

IP Rating

550mm 25 to 30 people / minute 5 million cycles

Brush motor Unidirectional or bidirectional CE and FCC

304 brushed stainless steel

1.5mm 1.0mm

304 brushed stainless steel

1.0mm

1,200 x 280 x 1,000 mm

 $(L \times W \times H)$

IP54 suitable for indoor / outdoor applications

INTERFACE

Communication Input

SAFETY

Sensors Anti-clamping Anti-tailgating Anti-reverse passing Illegal entry alarm

ELECTRICAL

Operating voltage

Operating power

RS485 Dry contact

Yes Yes Yes Yes


Visual alarm

110VAC ~ 220VAC ±10% (50Hz ~ 60Hz)

40 Watt

Dimensions





Ordering Information

VX-TURN-SS-550-01

Standard Tripod Turnstile with 550mm Passage Width

Email

Website

