

### **HEAVY DUTY VEHICLE BARRIER WITH 4.5 METER**

## VX-BAR-HD-F45M

Heavy Duty Vehicle Barrier with 4.5 Meter Folding Arm with IP54 Controller and Logic Board Enclosure, Foundation Plate, Loop Detector, Vehicle Photocell Sensor and Manual Push to Open Button, used for low ceiling areas with heavy traffic flow



## **Specifications**

#### **OPERATIONAL**

Arm length Opening Speed

Fastest Opening Speed Mean Cycles Between Failure Orientation

Certification

4.5 Meter (When straight)

(0.25, 0.35 and 0.6 seconds) 0.25 seconds for 4.5 meter arm

Left or right

(selectable at purchase)

CE

#### STRUCTURE

Material
Arm Material
Amr Thickness
Dimensions
Clearance
(Arm to ground)
Operating Temperatu

Color

304 brushed stainless steel High impact polycarbonate 12mm

340 x 305 x 1050 mm (L x W x H)

850 mm

-20 °C to +75 °C IP54 suitable for indoor outdoor applications Silver and black

#### **MOTOR**

Motor Type Motor Power Speed Control

**Operating Capacity** 

DC Brushless Motor 160 Watt Step-less Speed Change using DC Gear Drive 24 / 7 Operation

#### **INTERFACE**

Communication Input Manual Counter Traffic light RS485 Dry contact Push button Optional Optional

#### **SAFETY**


Photocell sensor Ground loop detector Auto-reverse Yes Yes Yes


#### **ELECTRICAL**


Operating voltage

(50Hz ~ 60Hz) Operating power 160 Watt

## **Dimensions**







# Ordering Information

5063 Commercial Circle,

Concord, CA 94520

**United States** 

VX-BAR-HD-F45M

Adkinns

HO

Heavy Duty Vehicle Barrier with 4.5 Meter Folding Arm